


LED-LOGO 丸型両面Outdoor Display



NovaStar社のTaurusT1を使用し、携帯アプリでの映像配信が可能。取付や設定も容易。店舗看板演出や丸型用演出としてご利用ください。

规格参数——Specifications

Pixel composition像素组成	1R1G1BLED (SMD1921)	(SMD3535)
Pixel pitch像素间距	4.6mm	8mm
Module size模组尺寸	300mm*300mm	320mm*320mm
Module resolution模组分辨率	64X64	40×40
LED package form灯珠封装形式	Kinglight / Nationstar	
Display density显示屏像素/面	128*128dots/side	80*80dots/side
Maximum white balance brightness 亮度	≥4500 cd/m ²	
Gray level灰度等级	Red, green, and blue ≥ 256 levels, up to 65536 levels	
Out of control points失控点	≤1/10000	
Optimal viewing distance最佳观看距离	≥4.68M	
Viewing angle视角	Level: ≥120°Vertical≥120°	
Device driver扫描方式	1/8 Scan	1/5 Scan
Change frame frequency换帧频率	≥60Hz	
Refresh rate刷新率	≥1920Hz	
Control method控制方式	Asynchronous/synchronous(wifi/4G cloud sevice/computer etc	
Waterproof grades and materials防水等级	Ip65	
Lifetime寿命	≥100,000 hours	
Operating Voltage工作电压	AC 110V-220V±15%, 50Hz±2Hz	
Environmental temperature and humidity 温度/湿度环境	Temperature: -20°C~+60°C, Humidity: 10%-95%	
Smoothness平整度	adjustment image between ≤0.5mm; module splicing gap ≤0.5mm	
Power consumption (maximum/average)功耗	400W/Pcs	
Maintenance method维护方式	Front-maintenance	
Screen weight屏体重量	≤16Kg/Pcs	
Switching power supply电源	5V/60A	

ニッシントーア・岩尾株式会社
産業資材部